


SPECIFICATION	
Current	700mA
Power	2. 1W/LED module

(NOTE)  
Do not work on live circuits!  
Excessive current will cause the LED to break

(NOTE 2)  
Maximum number of LED will be depending on the power supply to be used.

(NOTE 3)  
Fixtures may have any increment of LED modules (maximum depending on the power supply) in 60mm , 75mm, and 100mm spacing.



※Glare cut louver may be located on either side of the fixture.

7			
6	Glare Cut Louver	AL	Surface Treatment : Black Anodized Aluminium. Glare Cut off Angle: 33°
5	Electrical Wire		AWG20 × 2 [ Red + , Black - ]
4	End Plate	PC	Black
3	Top Cover	AL	Surface Treatment : Black Anodized Aluminium.
2	Extruded Fixture	AL	Surface Treatment : Black Anodized Aluminium.
1	LENS		Beam Angle: SP ( 40° × 15° ) , 15° Custom : 8° , 25° , 35°
	LED		Color Temperature : , 2700K, 3000K, 4000K Custom : 2200K , 3500K, 5000K
No.	部品 Parts	材料 Material	備考 Memo

Note : Lutron Eco-System Driver Recommended  
Maximum no of LED : 15pcs

Date 日付	2015. 12. 3	Scale 縮尺	1:1	Title	GRHB WITH GLARE CUT LOUVER
Draft 製図	T. Hirai	Weight 重量	xxkg/()	名称	GRHB-**-****K-**
Check 検図	D. Miwa	Unit 単位	mm	Product No.	GRHB-GLVR
Approve 承認	C. Ishibiki	Size 用紙	A3	製品番号	GRHB-GLVR
				<b>TOKI CORPORATION</b>	
				Tel 03-5763-6121 Fax 03-5763-6130	