

1

2

3

4

5

6

REV

DATE

7

8

APPROVED

CHECKED

REVISED

SPECIFICATIONS

CURRENT : 700mA

POWER : 2.1W/LED

<<PROHIBITION>>

Do not work on live circuits! Excessive current will cause the LED to break.

※ LED constant current power supply is required.

(※1)

Lens pitch "P" will be three types.

60mm pitch, 75mm pitch, 100mm pitch

1

2

3

4

5

6

200

P/2

P

P

L=no of LED x Pitch (P)

Red: +

Black: -

15.2

30

5.2

Bracket mounting dimensions

Scale1 : 1

45

26

7

6

5

4

3

2

1

No.

FIX BRACKET

ELECTRIC WIRE

END PLATE

TOP COVER

EXTRUDED SHAPES

LENS

LED

PARTS

SUS

PC

AL

AL

MATERIAL

AWG20×2 [RED + , BLACK -]

Surface treatment: Matte black

Surface treatment: Black almite

Surface treatment: Black almite

Light distribution:
SP (40° ×15°) ,15° (BTO : 8° ,25° ,35°)

Color temperature:
2700K, 3000K, 4000K (BTO : 2200K, 3500K, 5000K)

MEMO

Note : Lutron Eco-System Driver Recommended

Maximum no of LED : 15pcs

DATE

2015/10/9

DESIGNED

T. Hirai

CHECKED

T. Inaba

APPROVED

C. Ishibiki

TREATMENT FINISH

MATERIAL

UNIT

mm

SCALE

1 : 1

PRODUCT No.

GRHB-***-****K-**

GRHB-FIXB*

TITLE

Gradient HB

DRAWING NO.

REV

1

TOKI CORPORATION CO., LTD.

TEL:03-5763-6121 FAX:03-5763-6130

A3