REV	DATE	REVISION DESCRIPTION	APPROVED	CHECKED	REVISED

SPECIFICATIONS

CURRENT : 700mA

POWER : 2.1W/LED

<<PROHIBITION>>

Don't please absolutely live line work. A lighting apparatus breaks in an instant!

※Another LED constant current power supply is required.

※The number of the maximun LEDs depends on a LED driver.

(※1)
Lens pitch "P" will be three types.
60mm pitch, 75mm pitch, 100mm pitch





Bracket mounting dimensions
Scale1 : 1



No.	PARTS	MATERIAL	MEMO
7			
6	FIX BRACKET	SUS	
5	ELECTRIC WIRE		AWG20×2 [RED + , BLACK −]
4	END PLATE	PC	Surface treatment: Matte black
3	TOP COVER	AL	Surface treatment: Black almite
2	EXTRUDED SHAPES	AL	Surface treatment: Black almite
1	LENS		Light distribution: SP (40° ×15°) ,15° (BTO : 8° ,25° ,35°)
	LED		Color temperature: 2700K, 3000K, 4000K (BTO : 2200K, 3500K, 5000K)

DATE	2015/10/9	TREATMENT FINISH	****
DESIGNED	T. Hirai	MATERIAL	****
CHECKED	T.Inaba	UNIT	mm
APPROVED	C.Ishibiki	SCALE	1:1

PRODUCT No. GRHB-**-****K-**
GRHB-FIXB*

TITLE Gradient HB

DRAWING NO. **** REV 1

TOKI CORPORATION CO., LTD. TEL:03-5763-6121 FAX:03-5763-6130

A3