

PROVISIONAL

SPECIFICATIONS

CURRENT : 700mA
POWER : 2.1W/LED
LIGHT CONTROL : LUTRON EcoSystem



<<PROHIBITION>>

Don't please absolutely live line work. A lighting apparatus breaks in an instant !


*Another LED constant current power supply is required.

(※1)

Lens pitch "P" will be three types.
60mm pitch, 75mm pitch, 100mm pitch



Bracket mounting dimensions
Scale1 : 1



7	PARALLEL LOUVER	PC	Glare cutoff angle : Parallel_50° back_55°
6	FIX BRACKET	SUS	
5	ELECTRIC WIRE		AWG20×2 [RED + , BLACK -]
4	END PLATE	PC	Surface treatment: Matte black
3	TOP COVER	AL	Surface treatment: Black almite
2	EXTRUDED SHAPES	AL	Surface treatment: Black almite
1	LENS		Light distribution: SP (40° ×15°) , 8° , 15° , 25° , 35°
	LED		Color temperature: 2200K, 2700K, 3000K, 3500K, 4000K, 5000K
No.	PARTS	MATERIAL	MEMO

Total length "L"	Bracket mounting interval
300~799 (mm)	250 (mm)
800~1499 (mm)	500 (mm)
1500 (mm) ~2400 (mm)	1000 (mm)

DATE 2015/3/11

DESIGNED T. Hirai

CHECKED T. Inaba

APPROVED C. Ishibiki

TREATMENT FINISH ****

MATERIAL ****

UNIT mm SCALE 1:1

TOKI CORPORATION CO., LTD.

PRODUCT No. GRHB-**-****K-**-**
GRHB-PLVR + GRHB-FIXB2-OP

TITLE DP-00072 Gradient HB

DRAWING NO. **** REV 1

TEL:03-5763-6121 FAX:03-5763-6130