



TOKISTAR LIGHTING SYSTEMS



Please maintain 100mm distance or more from the tip of the lamp to the object to be illuminated. In this way, discoloration and deterioration of the object will be avoided.

Product Code	Lamp Pitch	Power	Max no. of Lamps	Weight
RW-50-__	50 ± 2	36w/m	176lamps	630g/m
RW-75-__	75 ± 3	24w/m	176lamps	460g/m
RW-100-__	100 ± 4	18w/m	176lamps	370g/m

REVELER SPECIFICATION

Rated Voltage	: AC24V
Power Consumption	: 1.8W/lamp
Color Temperature	: 2700Kelvin : 3000Kelvin : 5000Kelvin : 2400Kelvin(per order) : 4200Kelvin(per order)
Beam Angle	: 120D 120° : SP Spread

6			
5			
4	Lead Wire		AWG14 X 2 Black
3	End Cap	PVC	Black
2	Body		Aluminum die-cast,PBT Black
1	Lens		Len120° or SP Beam Angle· non replacable, PC
No.	Parts 部品	Material 材料	Memo 備考

Date 日付 2015/4/28

Draft 製図 K. Ashikaga

Check 検図 T. Shimamura

Approve 承認 C. Ishibiki

Scale 縮尺